



Vane anemometer

testo 410 – Pocket-sized flow velocity measuring instrument

Flow velocity measuring instrument with temperature measurement

Integrated measurement with 30 mm vane

Time mean value calculation

Hold function and max./min. values

Windchill calculation for outdoor areas

Additional advantages testo 410-2: Air humidity measurement with long-term stable Testo humidity sensor



Illustration 1/1

The vane anemometers testo 410-1 and testo 410-2 offer perfect flow velocity measurement results in handy pocket format. The small, user-friendly testo 410-1 measures air flow velocity and temperature, and is suitable for fast spot checks on ventilation outlets thanks to the integrated measurement with the 30 mm vane. A timed mean value calculation is also possible. The measuring instrument has an illuminated display, a clip-on protective cap, and a wrist strap and a belt holder ensure safekeeping.

In addition to air flow velocity and air temperature, the testo 410-2 also measures air humidity. This allows air conditions to be tested reliably. In addition to this, dewpoint and wet bulb are calculated and displayed fully automatically.



Technical data / Accessories

testo 410-1

testo 410-1 handy vane anemometer with integrated NTC air thermometer incl. protection cap, batteries and calibration protocol

Part no. 0560 4101



General technical data

Dimensions	133 x 46 x 25 mm (incl. protective cap)
Operating temperature	-10 to +50 °C
Storage temperature	-20 to +70 °C
Protection class	IP10
Battery type	2 AAA micro batteries
Weight	110 g (with protective cap and batteries)
Measuring rate	0.5 s

testo 410-2

testo 410-2 handy vane probe anemometer with integrated humidity measurement and NTC-air thermometer incl. protection cap, batteries and calibration protocol

Part no. 0560 4102



Technical data	testo 410-1/-2		testo 410-2
Sensor types	Vane	NTC	Testo humid. sensor, cap.
Measuring range	0.4 to 20 m/s	-10 to +50 °C	0 to 100 %RH
Accuracy ±1 digit	±(0.2 m/s + 2% of m.v.)	±0.5 °C	±2.5 %RH* (5 to 95 %RH)
Resolution	0.1 m/s	0.1 °C	±0.1 %RH
Battery life	100 h (average, without display illumination)		60 h (average, without display illumination)

*Please see the additional accuracy information for humidity in the instruction manual.

Accessories for measuring instrument	Part no.	
ISO calibration certificate velocity two point calibration; calibration points 5m/s and 10m/s	0520 0094	
ISO calibration certificate velocity hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034	

Lindab Ltd

Lindab Ventilation Branches

Aberdeen	01224 708582	Exeter	01626 835032	Manchester	0161 876 0688
Basildon	01268 532016	Gateshead	0191 482 5995	Norwich	01603 747532
Belfast	02890 781607	Glasgow	0141 419 3800	Nottingham	0115 985 1923
Birmingham	0121 552 6100	High Wycombe	01494 463490	Sheffield	0114 244 5444
Bristol	0117 977 1345	Kent	01474 579800	Southampton	02380 262111
Cardiff	02920 794503	Leeds	0113 297 1111	Stoke-on-Trent	01782 383460
Croydon	0208 603 0850	Leicester	0116 255 6044		
Enfield	0208 805 3656	Lincoln	01522 567087		

Email: sales@lindab.co.uk
Web: lindab.co.uk
Eshop: lindab.co.uk/eshop